

THE STATIONARY MOTORIZED LARGE VENUE SCREEN FOR TRADE SHOWS, CONFERENCE HALLS, THEATERS AND CINEMAS

Housing made of coated sheet steel, 1 mm thick, with square cross section. Colour of housing and bottom weight profile: white, RAL 9003

Mounting brackets for direct ceiling installation are included in delivery, mounts for wall mounting optionally available

The trapezoidal bottom weight profile closes the protective housing flush when rolling up the screen surface; essential for integration in suspended ceilings. The bottom weight profile is equipped with an integrated equalization system

Easy and safe handling due to an electrical drive

Automatic electrical end switch at the top and bottom

With a sturdy maintenance-free tubular motor 230 Volt/50 Hz, protective class IP44, four wire connection, built-in thermal protection

Body-sound-insulated, maintenance-free special winding shaft, secured against torsion at the motor side, low noise and vibration-free

Motor and cable entry at the right from the point of viewer

In-wall switch (Up/Stop/Down)

Installation frame for integration in suspended ceilings as optional

Customized sizes, special colour of casing, different types of screens surfaces on request



Metal construction of housing coated with colour RAL-9003



The trapezoidal bottom weight profile for integration in suspended ceilings



Mounting brackets for direct ceiling installation

Mod	Overall / Image size in cm (W x H)	Code no.	Weight gross/net in kg	Package size in cm	Cross section in cm	Screen surface
350	350x250 / 350x250	31001	108/53	410x25x35	15	Blankora Supra
	350x300 / 350x300	31009	108/53	410x25x35	15	Blankora Supra
400	400x300 / 400x300	31011	125/60	460x25x35	15	Blankora Supra
	400x400 / 400x400	32156	160/80	460x30x40	20	Blankora Supra
500	500x400 / 500x400	32160	185/95	560x30x40	20	Blankora Supra
600	600x400 / 600x400	32163	205/105	660x30x40	20	Blankora Supra
700	700x500 / 700x500	33075	250/180	760x37x47	27	Blankora Supra
800	800x500 / 800x500	33085	280/200	860x37x47	27	Blankora Supra
900	900x600 / 900x600	34096	400/310	960x46x56	36	Blankora Supra
1000	1000x600 / 1000x600	34106	450/350	1060x46x56	36	Blankora Supra
1100	1100x600 / 1100x600	34116	510/400	1160x46x56	36	Blankora Supra